

A Grammar is nothing but a set of rules to define valid sentences in any language, here we are introducing Context free grammars, which generate Context free languages. CFL has great practical significance in defining programming language and in simplifying the translation for programming languages.

Context free grammars :-

Mathematically Context free grammar is defined as follows

A Grammar $G = (V, T, P, S)$ is said to be Context free.

Where

V = A finite set of Non-terminal (variable), generally represented by Capital letters $A, B, C, D, \dots$

T = A finite set of terminal, generally represented by small letters, like $a, b, c, d, e, f, \dots$

S = Starting non-terminal (variable), called start symbol of the grammar, $S \in V$

P = Set of rules or production in CFG.

G is a Context free and all production in P have the form

$$\alpha \rightarrow \beta$$

Where. $\alpha \in V$ & $\beta \in (V \cup T)^*$

Note: Regular
Every Grammar is Context free, so a regular language is also a Context free one. It is already proved by Pumping lemma that language $\{a^n b^n \mid n > 0\}$ is not regular but it is possible to design a CFG for these language.

"So it is very clear that "The family of regular language is a proper subset of the family of CFL"

Ex 1: Consider a grammar $G = (V, \Sigma, P, S)$ where
(Lecture 2, 03)

Q.1. Construct a CFG for language $L = \{a^n b^n \mid n \geq 1\}$

Ans: $G = (V, \Sigma, P, S)$

$$V = \{S\}$$

$$\Sigma = \{a, b\}$$

$$P \rightarrow S \rightarrow aSb \mid ab$$

Q.2. Construct a CFG for language $ww^R \mid w \in (a, b)^+$

Ans: $G = (V, \Sigma, P, S)$

$$V = \{S\}$$

$$\Sigma = \{a, b\}$$

$$P \rightarrow S \rightarrow aSa \mid bSb \mid a \mid b \mid \epsilon$$

Q.3. Write a CFG, which generate palindrome for binary no.

Ans: $G = (V, \Sigma, P, S)$

$$V = \{S\}$$

$$\Sigma = \{0, 1\}$$

$$P \rightarrow S \rightarrow 0S0 \mid 1S1 \mid 0 \mid 1 \mid \epsilon$$

Q. Design a CFG for the language $L = \{a^n b^m : n \neq m\}$

Ans: If $n \neq m$ then there are only two cases are possible

Case 1. if $n > m$

$$L_1 = \{a^n b^m : n > m\}$$

$$G_1 = (V_1, T_1, P_1, S_1)$$

$$V_1 = \{S_1, A, S_1'\}$$

$$T_1 = \{a, b\}$$

$P \rightarrow$

$$S_1 \rightarrow A S_1'$$

$$S_1' \rightarrow a S_1' b \mid \epsilon$$

$$A \rightarrow a A \mid a$$

Case 2:

if $n < m$

$$L_2 = \{a^n b^m : n < m\}$$

$$G_2 = (V_2, T_2, P_2, S_2)$$

$$S_2 = S_2' B$$

$$S_2' = a S_2' b \mid \epsilon$$

$$B \rightarrow b B \mid b$$

$$V_2 = \{S_2, B, S_2'\}$$

Final Grammar for language L

$$S \rightarrow S_1 \mid S_2$$

Q.4. Construct a CFG for set of all string of length 2 for $\Sigma = \{a, b\}$

Ans.

$$G = (V, \Sigma, P, S)$$

$$V = \{S, A\}$$

$$\Sigma = \{a, b\}$$

$P \rightarrow$

$$S \rightarrow AA$$

$$A \rightarrow a|b$$

Q.8. Construct the CFG for the language $L = \{wcnw^R \mid w \in (a,b)^+\}$

Ans.

$$G = (V, \Sigma, P, S)$$

$$V = \{S\}$$

$$\Sigma = \{a, b\}$$

$P \rightarrow$

$$S \rightarrow aSa | bSb | c$$

Parse Tree : (Derivation Tree):

(Lecture-04)

①

There is a tree representation for derivation that has proved extremely useful.

A Parse Tree is an ordered tree in which nodes are labeled with the left side of productions and in which the children of a node represent its corresponding right side.

Definition:

Let $G = (V, T, P, S)$ be a CFG. An ordered tree for this CFG, G is a derivation tree if and only if it has the following properties.

- (a) The root is labeled by the starting non-terminal of the CFG that is S .
- (b) Every leaf of the ordered tree has a label from $T \cup \{\epsilon\}$.
- (c) Every interior node of ordered tree has a label from V .
- (d) Let us assume that a vertex has label $x \in V$, and its children are labeled (from left to right) $y_1, y_2, y_3, \dots, y_n$. Then production must contain a production of the form

$$x \rightarrow y_1 y_2 \dots y_n$$

- (e) A leaf labeled ϵ has no siblings, that is, vertex with a child labeled ϵ can have no other children. Clearly if the leaf is labeled ϵ , then it must be the only child of its parent.

The yield of parse tree:

If we look at the levels of any parse tree and can concatenate them from the left, we get a string, called the yield of the tree. Which is always a string that is derived from the root will be proved shortly of special importance are those parse tree such that

- (a) The yield is a terminal string. All leaves are labeled either with a terminal or with ϵ .

(b) The root is labeled by the start symbol.

Ex. 1. Consider the CFG

$$S \rightarrow XX$$


$$X \rightarrow XXX | bX | Xb | a$$

Find the parse tree for the string bbaaaab

Sol.

$$S \rightarrow XX$$

$$X \rightarrow XXX | bX | Xb | a$$



Q.2 Consider the grammar G, with productions


$$S \rightarrow aXY$$

$$X \rightarrow bYb$$

$$Y \rightarrow X | \epsilon$$

Find the parse tree for the string abbbb

Sol.



Q3. Write a CFG for a language $L = \{x0^n y 1^n z \mid n \geq 0\}$ and give the parse tree for the string $x000y111z$

Ans.

CFG: $G(V, \Sigma, P, S)$


$V = \{S, B\}$

$\Sigma = \{x, y, z, 0, 1\}$

$P \rightarrow$

$S \rightarrow xBz$

$B \rightarrow 0B1 \mid y$



$x000y111z$

Q.4.

Consider the CFG for the string aabbba

(14)

$$S \rightarrow aAS|a$$

$$A \rightarrow SbA|ba$$

Leftmost:

$$S \rightarrow aAS$$

$$\cancel{S \rightarrow aAS} A \rightarrow SbA$$

$$a \underline{S} bAS$$

$$S \rightarrow a$$


$$a a b AS$$

$$A \rightarrow ba$$

$$a a b b a S$$

$$S \rightarrow a$$

$$a a b b a a$$



Rightmost:

$$S \rightarrow aAS$$

$$S \rightarrow a$$


$$\rightarrow a \underline{A} a$$

$$A \rightarrow SbA$$

$$\rightarrow a Sb \underline{A} a$$

$$\rightarrow a Sb b a a$$

$$\rightarrow a a b b a a$$




Ambiguity in grammars & language:

A CFG is called ambiguous if for at least one word in the language that it generates there are two possible derivations of the word that correspond to different syntax tree. If CFG is not ambiguous, it is called unambiguous.


R.T.O

Ex. If CFG is $S \rightarrow S + S \mid S * S \mid a \mid b$, show that G is ambiguous.




Ex. If CFG is $S \rightarrow aSb \mid SS \mid \epsilon$, show that G is ambiguous for $aabb$.

Ans.



Ex. If CFG G is $S \rightarrow aSbS \mid a$, show that G is ambiguous for $abababa$.

Ans



Removing Ambiguity for Grammars:

⑥

- * If a CFG is ambiguous, it is often possible & usually desirable to find an equivalent unambiguous CFG.
- * Although some CFG are "inherently ambiguous" in the sense that they cannot be produced except by ambiguous grammar.
- * Ambiguity is usually the property of the grammar rather than the language.

Grammar for
Let's consider the algebraic expression and for the string $a+a*a$ the two parse trees are possible





Fig-1.

In the above grammar the precedence of the operator $+$ & $*$ is the cause of ambiguity.

The parse tree for string $a+a*a$ are



(7)

The Cause of ambiguity in string $a+a+a$ is the associativity of $+$ operator. If we assume the $+$ operator is left associative the string $a+a+a$ is equivalent to $(a+a)+a$.

* We see $E \rightarrow E+E$, by itself is enough to produce ambiguity. ^{we need} so the need to sum of something.

* The word 'terms' to stand for the things that are added. The Grammar will be, $E \rightarrow E+T \mid T$

* The Expression can also be products; like $a+b*c$ and $a*b+c$ are both sums, so it is right to say that term can be product.

* The factor are the things that are multiplied to produce terms.

$$T \rightarrow T * F \mid F.$$

→ The corresponding variable in the grammar will be F

* Since the Multiplication have higher precedence over addition, we can say that Expression are sum of one or more terms, & terms are products of one or more factors.

* Now, we must deal with Parentheses, we might say that (E) could be an expression, a term or a factor. However, evaluation of a Parenthetical Expression takes precedence over any operator outside the parentheses. Factors are evaluated first in hierarchy.

→ The resulting unambiguous grammar is

$$E \rightarrow E+T \mid T$$

$$T \rightarrow T * F \mid F$$

$$F \rightarrow (E) \mid a$$

— identifier (id)

Simplified CFG and Its Normal FormsReduction of CFG:

There are several ways in which one can restrict the format of CFG without reducing the language generation power. Let L be a CFL, then it can be generated by a CFG G with the following properties.

- We must eliminate useless symbols. those variable or terminal that do not appear in any derivation of a terminal string from the start symbol.
- We must eliminate ϵ -productions, those of the form $\alpha \rightarrow \epsilon$ for some variable α .
- We must eliminate unit production, those of the form $\alpha \rightarrow \gamma$ for variable α and γ .

1. Eliminate Useless Symbols:

A symbol that is useful will be both generating and reachable. If we eliminate the symbols that are not generating first, and then eliminate from the remaining grammar those symbols that are not reachable. then after this process, CFG will have only useful symbols.

There for reduction of a given grammar G , involves following steps:

- Identified non-generating symbols in given CFG and eliminate those productions which contain non-generating symbols.
- Identified non-reachable symbols in grammar and eliminate those productions which contain non-reachable symbols.

Ex. Consider a CFG

$$\begin{aligned} S &\rightarrow AB \mid a \\ A &\rightarrow b \end{aligned}$$

Identified & eliminate useless symbols

Ans.

$$S \rightarrow AB|a$$

$$A \rightarrow b$$

Here B is non-generating so eliminate the production of B

$$S \rightarrow a$$

$$A \rightarrow b$$

Now A is not reachable the eliminate it

$$S \rightarrow a$$

Q. Remove the useless symbols from the given CFG

$$S \rightarrow aB|bX$$

$$A \rightarrow BAd|bSX|a$$

$$B \rightarrow aSB|bBX$$

$$X \rightarrow SBd|aBx|ad$$

Ans:

B is not generation symbol. It does not produce terminal in $w(t)$ and A is not reachable to remove both A & B from G.

$$S \rightarrow bX$$

$$X \rightarrow ad$$

Q. Consider the following grammar & obtain an equivalent grammar containing no useless grammar symbol.

$$A \rightarrow xyz|Xyzz$$

$$X \rightarrow Xz|xYz$$

$$Y \rightarrow yYy|xz$$

$$Z \rightarrow zy|z$$

Ans:

$A \rightarrow xyz$ and ~~$X \rightarrow Xz$~~ $Z \rightarrow z$ directly deriving to the string of terminal so it is useful symbol & X, Y do not lead to a string of terminal so remove X & Y production from G.

$$A \rightarrow xyz$$

(2)

$$Z \rightarrow zy|z$$

Now A is starting Non-terminal and in production of A does not contain Z, so Z is not reachable, so remove it from G.

$$A \rightarrow xyz$$

Q. Find the reduced grammar that is equivalent to the CFG given below

$$S \rightarrow aC | SB$$

$$A \rightarrow bSCa$$

$$B \rightarrow aSB | bBC$$

$$C \rightarrow aBC | ad$$

Ans:

$C \rightarrow ad$, so therefore, C is generating symbol, B is useless do not generate terminal and A is not reachable from start variable S. so eliminate A & B

$$S \rightarrow aC$$

$$C \rightarrow ad$$

Removal of Unit Production:-

A Production in the form of Non-terminal $\rightarrow$ One Non-terminal

That is the production in the form of $A \rightarrow B$ is called unit production.

Ex. Consider the CFG.

$$S \rightarrow AB$$

$$A \rightarrow a$$

$$B \rightarrow C | D$$

$$C \rightarrow D$$

$$D \rightarrow E$$

$$E \rightarrow a$$

Ans. In above production three unit productions

$$B \rightarrow C$$

$$C \rightarrow D$$

$$D \rightarrow E$$

then resolving unit productions.

$$S \rightarrow AB$$

$$A \rightarrow a$$

$$B \rightarrow c|b$$

$$C \rightarrow a$$

$$D \rightarrow a$$

$$E \rightarrow a$$

$$S \rightarrow AB$$

$$A \rightarrow a$$

$$B \rightarrow a|b$$

$$C \rightarrow a$$

$$D \rightarrow a$$

$$E \rightarrow a$$

Now C, D, E is not reachable production or useless production

$$S \rightarrow AB$$

$$A \rightarrow a$$

$$B \rightarrow a|b$$

Q. Consider the following unambiguous expression grammar

$$I \rightarrow a|b|2a|2b|2o|2i$$

$$F \rightarrow I|(E)$$

$$T \rightarrow F|T * F$$

$$E \rightarrow T|E + T$$

Ans. There are three unit productions.

$$T \rightarrow F$$

$$F \rightarrow I$$

$$E \rightarrow T$$

$F \rightarrow I$ remove by.

$$I \rightarrow a|b|2a|2b|2o|2i$$

$$T \rightarrow F|T * F \quad F \rightarrow (E)|a|b|2a|2b|2o|2i$$

$$E \rightarrow T|E + T$$

P.O

Now we eliminate $T \rightarrow \epsilon$ with the help of.

$$F \rightarrow (E) | a | b | Pa | Pb | Po | P,$$

Now Grammar

$$P \rightarrow a | b | Pa | Pb | Po | P,$$

$$F \rightarrow (E) | a | b | Pa | Pb | Po | P,$$

$$T \rightarrow T * F | (E) | a | b | Pa | Pb | Po | P,$$

$$E \rightarrow T | E + T$$

Now let us remove $E \rightarrow T$ with the help of

$$T \rightarrow T * F | (E) | a | b | Pa | Pb | Pa | P,$$

New Grammar

$$P \rightarrow a | b | Pa | Pb | Po | P,$$

$$F \rightarrow (E) | a | b | Pa | Pb | Po | P,$$

$$T = T * F | (E) | a | b | Pa | Pb | Po | P,$$

$$E \rightarrow E + T | T * F | (E) | a | b | Pa | Pb | Po | P,$$

Removal of ϵ productions:-

- Now for our attention to the eliminate the production of the form $A \rightarrow \epsilon$ which is called ϵ -production.
- If $A \in L(G)$, we cannot eliminate all ϵ -production from G , but if $\epsilon \notin L(G)$, we can eliminate all ϵ -productions from G .

To eliminate ϵ -productions from a grammar G we can use the following technique:-

If $A \rightarrow \epsilon$ is a production to be eliminated then we look for all productions, whose right side contain A , and replace each occurrence of A in each of these productions to obtain the non ϵ -production.

Q. Consider the following grammar.

$$S \rightarrow aA$$

$$A \rightarrow b| \epsilon$$

Ans! - Put the ϵ in place of A in right side of and new production added to

$$S \rightarrow aA|a$$

$$A \rightarrow b$$

Q. Consider the following grammar G.

$$S \rightarrow ABAC$$

$$A \rightarrow aA| \epsilon$$

$$B \rightarrow bB| \epsilon$$

$$C \rightarrow c| \epsilon$$

Ans 1.

Put the value of $A \in B \rightarrow \epsilon$ to the right side the new productions are.

$$S \rightarrow ABAC|BAC|ABC|BC|AAC|Ac|c$$

$$A \rightarrow aA|a$$

$$B \rightarrow bB|b$$

$$C \rightarrow c$$

Q. Consider the following grammar & remove ϵ -productions

$$S \rightarrow aSa$$

$$S \rightarrow bSb| \epsilon$$

Ans.

$$S \rightarrow aSa|bSb|aa|bb$$

CHOMSKY Normal form:-

if a CFG has only Production of the form

$$A \rightarrow BC$$

$$A \rightarrow a$$

is said to be chomsky normal form or CNF.

Q. Change the following Grammar $G = \{ \{S, A, B\}, \{a, b\}, P, S \}$

$$S \rightarrow bA|aB$$

$$A \rightarrow bAA|aS|a$$

$$B \rightarrow aBB|bS|a$$

into CNF.

Ans:

Ans:

CNF follow the property of Production is $A \rightarrow BC, A \rightarrow a$.

Some of the production do not follow the property of CNF. then we simplify it through adding some production

$$S \rightarrow X_bA | X_aB$$

$$A \rightarrow X_bAA | X_aS | a$$

$$B \rightarrow X_aBB | X_bS | a$$

$$X_a \rightarrow a$$

$$X_b \rightarrow b$$

Production $A \rightarrow X_aAA$ and $B \rightarrow X_aBB$ do not follow the property of CNF, $A \rightarrow BC$, so

~~$A \rightarrow X_aAA$~~

$$B \rightarrow X_aD$$

$$A \rightarrow X_bC$$

$$C \rightarrow AA$$

$$D \rightarrow BB$$

New Grammar

$$S \rightarrow X_aA | X_bB$$

$$A \rightarrow X_bD | X_aS | a$$

$$B \rightarrow X_aD | X_bS | a$$

$$X_a \rightarrow a$$

$$X_b \rightarrow b$$

$$C \rightarrow AA$$

$$D \rightarrow BB$$

Q. Change the following grammar into CNF.

$$S \rightarrow 1A \mid 0B$$

$$A \rightarrow 1AA \mid 0S \mid 0$$

$$B \rightarrow 0BB \mid 1$$

Ans.

Replace AA by C_a , and BB by C_b , and 1 by C_1 , 0 by C_0

$$S \rightarrow C_1A \mid C_0B$$

$$A \rightarrow C_1AA \mid C_0S \mid 0$$

$$B \rightarrow C_0C_b \mid 1$$

$A \rightarrow C_1AA$ do not follow the CNF Property.

$$\tilde{S} \rightarrow C_1A \mid C_0B$$

$$A \rightarrow C_1C_a \mid C_0S \mid 0$$

$$B \rightarrow C_0C_b \mid 1$$

$$C_a \rightarrow AA$$

$$C_b \rightarrow BB$$

$$C_0 \rightarrow 0$$

$$C_1 \rightarrow 1$$

Q. Change the following grammar into CNF

$$G = (\{S\}, \{a, b, c\}, \{S \rightarrow a|b|c|SS\}, S)$$

Ans.

$$S \rightarrow a|b|c|SS$$

Replace SS by D in production

$$S \rightarrow a|b|c|D$$

$$D \rightarrow SS$$

Q... Chang the following grammar into CNF

$$S \rightarrow abSb \mid a \mid aAb$$

$$A \rightarrow bS \mid aAAb$$

Ans.

Replace aA by Ba and $A**b**$ by B_b

$$S \rightarrow abSb \mid a \mid Ba_b$$

$$A \rightarrow bS \mid BaB_b$$

$$Ba \rightarrow aA$$

$$B_b \rightarrow Ab$$

Replace ab by C and Sb by D

$$S \rightarrow CD \mid a \mid Ba_b$$

$$A \rightarrow bS \mid BaB_b$$

$$Ba \rightarrow aA$$

$$B_b \rightarrow Ab$$

$$C \rightarrow ab$$

$$D \rightarrow Sb$$

Replace a by X_a and b by X_b

$$S \rightarrow CD \mid a \mid BaX_b$$

$$A \rightarrow X_bS \mid BaB_b$$

$$Ba \rightarrow aA$$

$$B_b \rightarrow Ab$$

$$C \rightarrow X_aX_b$$

$$D \rightarrow SX_b$$

$$X_a \rightarrow a$$

$$X_b \rightarrow b$$

Q. Convert CFG Which is given below into CNF form

$$S \rightarrow bA | aB$$

$$A \rightarrow bAA | aS | a$$

$$B \rightarrow aBB | bS | b$$

Sol.

Replace b by X_b and a by X_a

$$S \rightarrow X_bA | X_aB$$

$$A \rightarrow X_bAA | X_aS | a$$

$$B \rightarrow X_aBB | X_bS | b$$

$$X_a \rightarrow a$$

$$X_b \rightarrow b$$

Replace $X_aA \rightarrow C_a$ and $X_bB \rightarrow C_b$

$$\begin{aligned} S &\rightarrow X_bA | X_aB \\ A &\rightarrow X_bAA | X_aS | a \\ B &\rightarrow X_aC_b | X_bS | b \\ X_a &\rightarrow a \\ X_b &\rightarrow b \\ C_a &\rightarrow AA \\ C_b &\rightarrow BB \end{aligned}$$

Replace $X_bA \rightarrow C_a$ and $X_aB \rightarrow C_b$

$$\begin{aligned} S &\rightarrow X_bA | X_aB \\ A &\rightarrow C_aA | X_aS | a \\ B &\rightarrow C_bB | X_bS | b \\ C_a &\rightarrow X_bA \\ C_b &\rightarrow X_aB \\ X_a &\rightarrow a \\ X_b &\rightarrow b \end{aligned}$$

Q. Design a CFG for the language $L = \{a^{4n} \mid n \geq 1\}$ and convert that CFG into CNF form. (5)

Ans

Let CFG for the language $L = \{a^{4n} \mid n \geq 1\}$ is G .

$$G = (V, T, P, S)$$

$$V = \{S\}$$

$$T = \{a\}$$

$P \rightarrow$

$$S \rightarrow aaaaS \mid aaaa$$

Now let us convert this CFG into CNF form. replace each a by A then CFG

$$S \rightarrow AAAAS \mid AAAA$$

$$A \rightarrow a$$

the CFG form will be.

$$S \rightarrow AR_1$$

$$R_1 \rightarrow AR_2$$

$$R_2 \rightarrow AR_3$$

$$R_3 \rightarrow AS$$

$$S \rightarrow AR_4$$

$$R_4 \rightarrow AR_5$$

$$R_5 \rightarrow AA$$

$$A \rightarrow a$$

GRBIBACH NORMAL FORM:-

(Lecture-07)

For Every Context free language L without ϵ , there exist a grammar in which every production is of the form $A \rightarrow av^k$, where 'A' is a variable, 'a' is exactly one terminal ~~terminal~~ and 'v' is the string of none or more variable, clearly $v \in V_n^+$

Q. Convert the grammar

$$S \rightarrow AB|BC$$

$$A \rightarrow aB|bA|a$$

$$B \rightarrow bB|cC|b$$

$$C \rightarrow c$$

into GNF

Ans. Production $S \rightarrow AB|BC$ is not in GNF. On applying the substitution rule we get the grammar.

$$S \rightarrow aBbAB|aB|bBC|cCC|bC$$

in GNF.

Ex. Convert the grammar

~~$$S \rightarrow aBABA|aBA$$~~

$$S \rightarrow abaSa|aba$$

Ans. If we introduce new variable A and B and productions $A \rightarrow a$ & $B \rightarrow b$ & substitute into given grammar as.

$$S \rightarrow aBASA|aBA$$

$$A \rightarrow a$$

$$B \rightarrow b$$

Q... Convert the grammar

$$\begin{aligned} S &\rightarrow AB \\ A &\rightarrow BS|a \\ B &\rightarrow SA|b \end{aligned}$$

into CNF

Ans: The given grammar is in CNF, let us change the name of variable as A_1, A_2, A_3 for S, A, B respectively, Now the given productions are in the form (With A_1 as start symbol)

$$\begin{aligned} A_1 &\rightarrow A_2 A_3 \\ A_2 &\rightarrow A_3 A_1 | a \\ A_3 &\rightarrow A_1 A_2 | b \end{aligned}$$

In the above grammar we need production must start with terminal or with higher no. variable.

Applying substitution rule for A_1 then we get

$$A_3 \rightarrow A_2 A_3 A_2 | b$$

Applying substitution rule for A_2

$$A_3 \rightarrow A_3 A_1 A_3 A_2 | a A_3 A_2 | b$$

Eliminating the left recursion from A_3 production, we get

$$A_3 \rightarrow A_3 B_1 | a A_3 A_2 | b$$

$$B_1 \rightarrow A_1 A_3 A_2 B_1 | A_1 A_3 A_2$$

$$A_3 \rightarrow a A_3 A_2 B_1 | b B_1 | a A_3 A_2 | b$$

B_1 is new variable introduced.

Now all the A_3 Production start With terminals. With the help of Substitution rule
We can replace A_3 in R.H.S of A_2 Production.

$$A_2 \rightarrow aA_3A_2B_1A_1 \mid bB_1A_1 \mid aA_3A_2A_1 \mid bA_1 \mid a$$

Now, all A_2 Productions start With terminal. Again we replace A_2 from $A_1 \rightarrow A_2A_3$

$$A_1 \rightarrow aA_3A_2B_1A_1A_3 \mid bB_1A_1A_3 \mid aA_3A_2A_1A_3 \mid bA_1A_3 \mid aA_3$$


one Production $B_1 \rightarrow A_1A_3A_2B_1 \mid A_1A_3A_2$ is not in GNF. Now applying Substitution rule in Production.

$$B_1 \rightarrow aA_3A_2B_1A_1A_3A_3A_2B_1 \mid bB_1A_1A_3A_3A_2B_1 \mid aA_3A_2A_1A_3A_3A_2B_1 \mid bA_1A_3A_3A_2B_1 \mid aA_3A_3A_2B_1 \mid aA_3A_2B_1A_1A_3A_3A_2 \mid bB_1A_1A_3A_3A_2 \mid aA_3A_2A_1A_3A_3A_2 \mid bA_1A_3A_3A_2 \mid aA_3A_3A_2$$

All Productions are.

$$\begin{aligned} A_1 &\rightarrow aA_3A_2B_1A_1A_3 \mid bB_1A_1A_3 \mid aA_3A_2A_1A_3 \mid bA_1A_3 \mid aA_3 \\ A_2 &\rightarrow aA_3A_2B_1A_1 \mid aB_1A_1 \mid aA_3A_2A_1 \mid bA_1 \mid a \\ A_3 &\rightarrow aA_3A_2B_1 \mid bB_1 \mid aA_3A_2 \mid b \\ B_1 &\rightarrow aA_3A_2B_1A_1A_3A_3A_2B_1 \mid bB_1A_1A_3A_3A_2B_1 \mid aA_3A_2A_1A_3A_3A_2B_1 \mid bA_1A_3A_2B_1 \mid aA_3A_3A_2B_1 \mid aA_3A_2B_1A_1A_3A_3A_2 \mid bB_1A_1A_3A_3A_2 \mid aA_3A_2A_1A_3A_3A_2 \mid bA_1A_3A_3A_2 \mid aA_3A_3A_2 \end{aligned}$$

Ans



CHOMSKY HIERARCHY

UNIT III: (Important Questions)

1. Consider the grammar G given as follows : $S \rightarrow AB \mid aaB$ $A \rightarrow a \mid Aa$ $B \rightarrow b$, Determine whether the grammar G is ambiguous or not. If G is ambiguous then construct an unambiguous grammar equivalent to G.
2. The family of context free languages is closed under star-closure but is not closed under difference.
3. Given a context free Grammar G. Write an algorithm (if it exists) to determine whether $L(G)$ is infinite or not.
4. Given the following CFG having S as start symbol, find an equivalent CFG with no useless symbols : $S \rightarrow aAa \mid bSb \mid \epsilon$ $A \rightarrow C \mid a$ $B \rightarrow C \mid b$ $C \rightarrow CDE \mid \epsilon$ $D \rightarrow A \mid B \mid ab$.
5. Design the CFG for the following language: (UPTU 2018-19)
 - i) $L = \{0^m 1^n \mid m \neq n \text{ \& } m, n \geq 1\}$
 - ii) $L = \{a^l b^m c^n \mid l + m = n \text{ \& } l, m \geq 1\}$

Prove that the following language $L = \{a^n b^n c^n\}$ is not Context Free

6. What is difference between Chomsky normal form (CNF) and Greibach normal form (GNF) ? Convert the following grammar in Greibach normal form : $S \rightarrow AB$ $A \rightarrow BSB \mid BB \mid b$ $B \rightarrow a \mid aAb$. (UPTU 2013-14)
7. Find a Context Free Grammar (CFG) generating the following language : $L = \{a^i b^j c^k \mid i = j \text{ or } i = k\}$.
8. Describe the language generated by the following grammar : $S \rightarrow bS/aA/\epsilon$ $A \rightarrow aA/bB/b$ $B \rightarrow bS$.
9. Show that the given grammar is ambiguous. Also find an equivalent unambiguous grammar. $S \rightarrow ABA$ $A \rightarrow aA/\epsilon$ $B \rightarrow bB/\epsilon$. (UPTU 2013-14)
10. Given context free Grammar, how do you determine that grammar as : (i) Empty or Non Empty (ii) Finite or Non-Finite (iii) Whether a string x belongs to language of grammar. (UPTU 2012-13)
11. Design a CFG for the language consisting of all strings of even length over $\{a, b\}$.